

Invertec® V275-S

Processes

Stick, TIG, Gouging

Product Number

K2269-1

See back for complete specs

Input Power

208/230/460/575/3/60

Rated Output

275A/31V/35% Duty Cycle

Input Current @ Rated Output

38/37/19/16A

Output Range

5-275 Amps

Weight/Dimensions (H x W x D)

54.5 lbs. (24.7 kg)

13.6 x 9.0 x 20.25 in.


(345 x 229 x 514 mm)

Weather-Resistant Stick and TIG Welder


The Invertec® V275-S stick and TIG power source is ideal for outdoor construction sites—it's IP23S rated and equipped with weather resistant features. Up to 275 amps of output gives you access to a greater number of stick electrodes, including outstanding E6010 performance.

FEATURES

- ▶ **Outstanding AWS E6010 and E7018 performance** - using up to 7/32 in. (5.5 mm) diameter electrode that enables both whip and drag techniques for a variety of construction and fabrication applications.
- ▶ **Touch Start TIG®** - allows the welding arc to be established without high frequency starting.
- ▶ **Air carbon arc cutting and gouging** - with up to 3/16 in. (4.8 mm) diameter carbon electrode.
- ▶ **Selectable Hot Start** - turn it off for thin material or flip it on for thick, rusty or dirty material.
- ▶ **Variable Arc Force** - dial in the "soft" or "crisp" arc you want.



Soft Arc



Crisp Arc

- ▶ **All-in-one machine** - 208/220/230/380/400/415/440/460/575 input volt settings—no single phase de-rating.

APPLICATIONS

- ▶ Construction
- ▶ Fabrication
- ▶ Maintenance
- ▶ Repair



Shown:
K2269-1 Invertec® V275-S

WHAT'S INCLUDED

K2269-1 Includes:

- ▶ Invertec® V275-S
- ▶ Input Power Cable, 10 ft. (3.0 m)
- ▶ Twist Mate™ Cable Plugs (K852-70), quantity 2

K2666-1 V275-S (Tweco®) 4-Pack Inverter Rack

K2666-2 V275-S (Tweco®) 8-Pack Inverter Rack

For more information, see publication E5.92



Shown:
K2666-2 Invertec® V275-S
(Tweco®) 8-Pack Inverter Rack

INPUT



OUTPUT



Two Year Extended
Warranty Available in
the U.S.A. and Canada



The Lifting Professionals

Bolingbrook, IL
(630) 972-9199

South Holland, IL
(219) 972-9199

[Click Here to Request a Quote](#)



KEY CONTROLS

1. Preset Output Amps Control
2. Thermal Protection Indicator
3. "On" Light
4. Hot Start Control
5. On/Off Switch
6. Negative and Positive Output Terminals (Twist Mate™ or Tweco®)
7. Remote Output Control Receptacle - 6-Pin
8. Arc Control Knob
9. Mode Selection Switch (Stick/Touch Start TIG®)
10. Local/Remote Output Control



Shown:
K2269-3 Inverter® V275-S

RECOMMENDED ACCESSORIES

GENERAL OPTIONS



Caster Kit
Used on Inverter Racks.
Order K2665-1



Twist Mate™ Cable Plug
For connecting welding cable to output terminal receptacles. For 1/0-2/0 (50-70 mm²) cable.
Order K852-70



Twist Mate™ Cable Plug
For connecting welding cable to output terminal receptacles. For 2/0-3/0 (70-95 mm²) cable.
Order K852-95



Twist Mate™ Cable Receptacle
For connecting welding cable to Twist Mate™ cable plug. For 1/0-2/0 (50-70 mm²) cable.
Order K1759-70



Twist Mate™ Cable Receptacle
For connecting welding cable to Twist Mate™ cable plug. For 2/0-3/0 (70-95 mm²) cable.
Order K1759-95



STICK OPTIONS

Accessory Kit
For stick welding. Includes 35 ft. (10.7 m) 2/0 electrode cable with lug, 30 ft. (9.1 m) 2/0 work cable with lugs, headshield, filter plate, cover plate, work clamp and electrode holder. 400 amp capacity.
Order K704



Accessory Kit
For stick welding. Includes 20 ft. (6.1 m) #6 electrode cable with lug, 15 ft. (4.6 m) #6 work cable with lugs, headshield, work clamp, and electrode holder. 150 amp capacity.
Order K875



Remote Output Control
Consists of a control box with choice of two cable lengths. Permits remote adjustment of output. 6-pin connection.
Order K857 for 25 ft. (7.6 m)
Order K857-1 for 100 ft. (30 m)



TIG OPTIONS

17V Air-Cooled TIG-Mate™ Starter Kit
Get everything you need for TIG welding in one complete easy-to-order kit packaged in its own portable carrying case. Includes: PTA-17V Ultra-Flex™ torch, parts kit, Harris flowmeter/regulator, 10 ft. (3.0 m) gas hose, and work clamp and cable.
Order K2265-1



Twist Mate™ Torch Adapter
For connection of PTA-9 or PTA-17V torches (1 piece cable) to power sources without gas passing through the Twist Mate™ connection.
Order K960-1



Foot Amptrol™
Provides 25 ft. (7.6 m) of remote output control for TIG welding (6-pin plug connection).
Order K870



Hand Amptrol™
Provides 25 ft. (7.6 m) of remote current control for TIG welding. (6-pin plug connection). Velcro straps secure torch.
Order K963-3 (One size fits all Pro-Torch™ TIG Torches.)

PRODUCT SPECIFICATIONS

Product Name	Product Number	Input Power Voltage/Phase/Hertz	Rated Output Current/Voltage/Duty Cycle	Input Current @ Rated Output	Output Range	H x W x D inches (mm)	Net Weight lbs. (kg)
Inverter® V275-S	K2269-1	208/230/460/575/3/60	275A/31V/35% 250A/30V/60% 200A/28V/100%	38/37/19/16A 34/33/17/14A 27/25/13/11A	5-275A	13.6 x 9.0 x 20.25 (345 x 229 x 514)	54.5 (24.7)
or	or	208/230/460/575/1/60	275A/29-31V/35% 250A/30V/60% 200A/28V/100%	68/67/38/31A 63/62/33/27A 49/48/26/21A			
Inverter® V275-S (Tweco®) ⁽¹⁾	K2269-3	220/380/400/415/440/3/50	250A/30V/35% 200A/28V/100	32/20/19/18/17A 25/15/15/14/13A			
		220/380/400/415/440/1/50		63/42/40/38/36A 48/32/30/29/27A			

⁽¹⁾ With Tweco®-style output connectors. Tweco® is a registered trademark of Thermadyne.

For best welding results with Lincoln Electric equipment, always use Lincoln Electric consumables. Visit www.lincolnelectric.com for more details

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.

LINCOLN
ELECTRIC
THE WELDING EXPERTS®