

3232SEAC Electric Slim Scissor Lift

- Drives at Full Height Indoors
 Saving Time and Battery Energy
 Between Overhead Tasks
- Greater Productivity and Lower Cost of Ownership with Outrigger-Free Design
- AC Electric Drive for Extended Duty Cycles, Smoother Controls and Faster Drive Speeds
- Compact Maneuverability from Front Wheel Drive and Steer with Zero Inside Turn Radius
- Fully Proportional Lift and Drive Controls
- Standard Swing Gate
- Easy Serviceability with Swing Out Battery and Power Module Trays
- Maintenance-Free AGM Batteries



Metric

11.6 m*

U.S.

38 ft.*

Standard Features

Work Area

Roll-Out Deck Extension with Incremental Locking Positions Standard Swing Gate Lanyard Attachments (4)

Performance

Drive at Full Height Indoors No Outriggers AC Electric Drive Fully Proportional Drive and Lift Controls Up to 25% Gradeability

Power

Maintenance-Free AGM Batteries Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
Easy Maintenance Access to Mechanical and Electrical Components
in a Slide-Out Tray
Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

Dedicated Compartment Protects Electrical and Hydraulic Components
Emergency Shut-Off at Platform and Lower Controls
Non-Skid Metal Deck Construction
Descent Alarm
Drive Speed Interlock
Multi-Axis Tilt Sensor
Scissor Maintenance Lock

Other Features

Multiple Disc Brakes

Leak Containment System® (LCS) Removable Upper Controls Voltage-Compensating Fully Automatic Battery Charger Fold-Down Guardrails Hour Meter

Machine Tie Downs Non-Marking Tires All Motion Alarm Fork Lift Pocket Flashing Beacon (Continuous)

Optional Features

900W Inverter Tool Tray Cold Weather Package Proactive Platform Safety System® (PPSS) Upper Control Box Supplementary Guard Pipe Rack Second Year Extended Warranty

97043 DTD 0224



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520 Email: info@MECawp.com | www.MECawp.com

MEC®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® is Patent #11,112,060.

Outdoor Working Height*	30 ft.*	9.1 m*
Indoor Platform Height	32 ft.	9.8 m
Outdoor Platform Height	24 ft.	7.3 m
Stowed Height (Top Guardrail)	96 in.	2.4 m
Stowed Height (Rails Folded)	78 in.	2 m
Stowed Height (Platform Floor)	53 in.	1.3 m
Guardrail Height	43.5 in.	1.1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	4 in.	10 cm
Ground Clearance (Elevated)	0.7 in.	1.8 cm
Dimensions		
Length-Stowed (Overall)	97 in.	2.5 m
Length-Stowed (Ladder Removed)	89.5 in.	2.3 m
Chassis Width	32 in.	81 cm
Platform Length (Extended)	124.5 in.	3.2 m
Platform Length (Retracted)	89.5 in.	2.3 m
Roll-Out Deck Length	35 in.	90 cm
Platform Width	29 in.	74 cm
Wheelbase	74 in.	1.9 m
Total Lift Capacity	550 lbs	250 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs	113 kg
Speed		
Raise/Lower Speed	52 s / 38 s	
Drive Speed (Stowed)	3 mph	5 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
Performance		
Gradeability	25%	
Turning Radius (Inside)	0 in.	0 m
Weight**	7,145 lbs.	3240 kg
Power Source	24v 240Ah Maintenance-Free Batteries	
Controls	Proportional Drive & Lift Controls	
Tires	15 x 5 in.	38 x 13 cm
*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.		

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6 - 2017.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:

3232SEAG

Indoor Working Height*

Heights